



New energy Bearing Manufacturing Co.,...



80 mm x 125 mm x 22 mm SKF 7016 ACD/P4AH1 angular contact ball bearings

Bearing No. 7016 ACD/P4AH1

7016 ACD/P4AH1 Bearing 2D drawings and 3D CAD models

Size	125x80x22 mm
Bore Diameter	125 mm
Outer Diameter	80 mm
Width	22 mm
d	80 mm
D	125 mm
B	22 mm
d ₁	93.9 mm
d ₂	93.9 mm
D ₁	111.1 mm
K	0.5 mm
C ₁	5.89 mm
r _{1,2} - min.	1.1 mm
r _{3,4} - min.	0.6 mm
a	35 mm
d _a - min.	86 mm
d _b - min.	86 mm
D _a - max.	119 mm
D _b - max.	121 mm
r _a - max.	1 mm
r _b - max.	0.6 mm
d _n	96.9 mm
Basic dynamic load rating - C	62.4 kN
Basic static load rating - C ₀	58.5 kN



New energy Bearing Manufacturing Co.,...

Fatigue load limit - P_u	2.4 kN
Limiting speed for grease lubrication	9500 r/min
Limiting speed for oil lubrication	15000 mm/min
Ball - D_w	14.288 mm
Ball - z	20
G_{ref}	11.1 cm ³
Calculation factor - e	0.68
Calculation factor - Y_2	0.87
Calculation factor - Y_0	0.38
Calculation factor - X_2	0.41
Calculation factor - Y_1	0.92
Calculation factor - Y_2	1.41
Calculation factor - Y_0	0.76
Calculation factor - X_2	0.67
Preload class A - G_A	390 N
Preload class B - G_B	780 N
Preload class C - G_C	1560 N
Preload class D - G_D	3120 N
Calculation factor - f	1.13
Calculation factor - f_1	0.99
Calculation factor - f_{2A}	1
Calculation factor - f_{2B}	1.02
Calculation factor - f_{2C}	1.05
Calculation factor - f_{2D}	1.08
Calculation factor - f_{HC}	1
Preload class A	223 N/micron
Preload class B	291 N/micron
Preload class C	386 N/micron



New energy Bearing Manufacturing Co.,...

Preload class D	523 N/micron
d_1	93.9 mm
d_2	93.9 mm
D_1	111.1 mm
C_1	5.89 mm
$r_{1,2}$ min.	1.1 mm
$r_{3,4}$ min.	0.6 mm
d_a min.	86 mm
d_b min.	86 mm
D_a max.	119 mm
D_b max.	121 mm
r_a max.	1 mm
r_b max.	0.6 mm
d_n	96.9 mm
Basic dynamic load rating C	62.4 kN
Basic static load rating C_0	58.5 kN
Fatigue load limit P_u	2.45 kN
Attainable speed for grease lubrication	9500 r/min
Attainable speed for oil-air lubrication	15000 r/min
Ball diameter D_w	14.288 mm
Number of balls z	20
Reference grease quantity G_{ref}	11.1 cm ³
Preload class A G_A	390 N
Static axial stiffness, preload class A	223 N/ μ m
Preload class B G_B	780 N
Static axial stiffness, preload class B	291 N/ μ m
Preload class C G_C	1560 N
Static axial stiffness, preload class C	386 N/ μ m



New energy Bearing Manufacturing Co.,...

Preload class D G_D	3120 N
Static axial stiffness, preload class D	523 N/ μ m
Calculation factor f	1.13
Calculation factor f_1	0.99
Calculation factor f_{2A}	1
Calculation factor f_{2B}	1.02
Calculation factor f_{2C}	1.05
Calculation factor f_{2D}	1.08
Calculation factor f_{HC}	1
Calculation factor e	0.68
Calculation factor (single, tandem) Y_2	0.87
Calculation factor (single, tandem) Y_0	0.38
Calculation factor (single, tandem) X_2	0.41
Calculation factor (back-to-back, face-to-face) Y_1	0.92
Calculation factor (back-to-back, face-to-face) Y_2	1.41
Calculation factor (back-to-back, face-to-face) Y_0	0.76
Calculation factor (back-to-back, face-to-face) X_2	0.67
Mass bearing	0.85 kg